

Product/Process Change (PCN) Notification

PCN Number: DOC-108321	Contact: Eric Cheong	
Date Issued: Feb 18th, 2022	Title: Sr. Director, Sales	
PCN Effective Date: Feb 18th, 2022	Phone: 1-858-869-0591	
Product(s) Affected: PE42420	Email: pcn@psemi.com	
Sample Availability: Feb 18th, 2022		
Change Control Board Approval #: CO-31706		
Change Category:		
☐ Wafer Fabrication Process	☐ Shipping/Labeling	
☐ Design/Mask Change	☐ Equipment	
☐ Singulation Process	☐ Material	
Assembly Process	□ Product Specification	
☐ Electrical Test	☐ Product End of Life	
☐ Manufacturing Site	Other - Ordering codes change	
Purpose of Change:		
PE42420 operating temperature range is extended fr	om +105°C to +125°C	
, , , ,		
Description of Change:		
Description of Change:		
Description of Change: This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension	, ,	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension	, some datasheet specification is revised as below.	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d	, some datasheet specification is revised as below.	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2	atasheet specification is revised as below. atasheet. 5dBm in Operating Ranges table	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revise	atasheet specification is revised as below. atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revis Operating temperature range is extended to +125°C	atasheet specification is revised as below. atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table.	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revise Operating temperature range is extended to +125°C Operating power 20 MHz is revised to 28dBm in Absorber	atasheet specification is revised as below. atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table. blute Maximum Ratings table.	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revis Operating temperature range is extended to +125°C	atasheet specification is revised as below. atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table. blute Maximum Ratings table.	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revise Operating temperature range is extended to +125°C Operating power 20 MHz is revised to 28dBm in Absorber	atasheet. SdBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table. Solute Maximum Ratings table. ed to 23dBm in Absolute Maximum Ratings table.	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revise Operating temperature range is extended to +125°C Operating power 20 MHz is revised to 28dBm in Absolution (RFX) is revised to 28dBm in Absolution (RFX) is revised.	atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table. 5dlute Maximum Ratings table. 6d to 23dBm in Absolute Maximum Ratings table. 6his product and ordering code remains same. 60) basis. For the exact timing of the order code	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revis Operating temperature range is extended to +125°C Operating power 20 MHz is revised to 28dBm in Abso Maximum peak power into termination (RFX) is revis There will be no change in form, fit and function of t pSemi manages inventory on a First-In First-Out (FIF	atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table. 5dlute Maximum Ratings table. 6d to 23dBm in Absolute Maximum Ratings table. 6his product and ordering code remains same. 60) basis. For the exact timing of the order code	
This is a notification to advise our customers that PE +105°C to +125°C. With this temperature extension Electrical Specification table at +125°C is added to d Maximum operating power (RFC-RFX) is revised to 2 Maximum peak power into termination (RFX) is revis Operating temperature range is extended to +125°C Operating power 20 MHz is revised to 28dBm in Abso Maximum peak power into termination (RFX) is revis There will be no change in form, fit and function of t pSemi manages inventory on a First-In First-Out (FIF	atasheet. 5dBm in Operating Ranges table ed to 20dBm in Operating Ranges table in Operating Ranges table. 5dlute Maximum Ratings table. 6d to 23dBm in Absolute Maximum Ratings table. 6his product and ordering code remains same. 60) basis. For the exact timing of the order code	



Product/Process Change (PCN) Notification

Customer Acknowledgement of Receipt:		
☐ Change Denied	Name:	
(Include explanation in		
comments section below)	Title:	
☐ Change Approved	Company:	
	Date:	
	Signature:	
Customer Comments:		