

## PEREGRINE MATERIAL DECLARATION FORM

<b>Product:</b>	PE4271
<b>Ordering Codes:</b>	4271-51, 4271-52
<b>Description:</b>	SPST CATV UltraCMOS Switch DC - 3000 MHz
<b>Package:</b>	6L DFN
<b>Environmental Compliance</b>	EU RoHS Directive 2002/95/EC, <b>REACH</b> - EU ECHA SVHC, <b>Arsenic Free</b> , <b>JIG 101</b> - EIA/EICTA/JEITA, <b>Halogen Free</b> - IEC61249-2-21, <b>PFOS Free</b> - 2006/122/EC, <b>Antimony Trioxide Free</b>
<b>Lead Finish</b>	100% Matte Tin
<b>Availability</b>	Now

Component	Material	CAS Number	Weight (mg)	%	PPM
<b>Die</b>					
	Sapphire (Al <sub>2</sub> O <sub>3</sub> )	1344-28-1	0.886712	4.11%	41,097
	Silicon (Si)	7440-21-3	0.000294	0.00%	14
	Arsenic (As)	7440-38-2	0.000001	0.00%	0
	Boron (B)	7440-42-8	0.000000	0.00%	0
	Phosphorous (P)	7723-14-0	0.000099	0.00%	5
	Titanium (Ti)	7440-32-6	0.000034	0.00%	2
	Tungsten (W)	7440-33-7	0.000003	0.00%	0
	Copper (Cu)	7440-50-8	0.000005	0.00%	0
	Aluminum (Al)	7429-90-5	0.001476	0.01%	68
	Cobalt (Co)	7440-48-4	0.000000	0.00%	0
<b>Package</b>					
Leadframe	Copper (Cu)	7440-50-8	7.795600	36.13%	361,312
	Iron (Fe)	7439-89-6	0.187900	0.87%	8,709
	Zinc (Zn)	7440-66-6	0.009600	0.04%	445
	Phosphorus (P)	7723-14-0	0.002400	0.01%	111
	Silver (Ag)	7440-22-4	0.206400	0.96%	9,566
Die Attach	Silver (Ag)	7440-22-4	0.199900	0.93%	9,265
	Epoxy Resin	9003-36-5	0.050000	0.23%	2,317
	t-Butyl phenyl glycidyl ether	3101-60-8	0.020800	0.10%	964
	Phenolic hardener	92-88-6	0.004200	0.02%	195
	Butyl cellosolve acetate	112-07-2	0.002800	0.01%	130
Gold Wire	Gold (Au)	7440-57-5	0.088500	0.41%	4,102
100% Matte Tin Lead Finish	Tin (Sn)	7440-31-5	0.114900	0.53%	5,325
Mold Compound	Silica Fused	60676-86-0	11.007800	51.02%	510,191
	Epoxy Resin	Trade secret	0.480200	2.23%	22,256
	Phenol Resin	Trade secret	0.480200	2.23%	22,256
	Carbon Black	1333-86-4	0.036000	0.17%	1,669
<b>Total Weight (mg)</b>			<b>21.575824</b>	<b>100.00%</b>	<b>1,000,000</b>